

EASY LEVEL
7 MM BY UNIFLOOR

Levelling underlay for a wooden subfloor

- Impact sound reduction in combination with click LVT and resilient vinyl
- Suitable for various floor finishes
- For domestic and commercial use
- Suitable for underfloor heating

Unifloor's Easylevel 7mm is an underlay suitable for wood and concrete bearing floors. This underlay is suitable for use in combination with underfloor heating and is perfectly suitable for LVT (click and loose lay), cushion vinyl and carpet tiles.

Easylevel has a total thickness of 7mm and has a great dry levelling capacity when used on a wooden substrate. The product is specially designed to create a stable base for your floor. Installation is simple and effortless. This underlay is more than just a stable and level base.

In combination with click LVT or cushion vinyl, Easylevel 7mm offers an impact sound reduction of up to 21 dB when used with a concrete subfloor! This underlay effectively muffles sound, allowing a pleasant living environment to be created without disturbing impact noise.

With Easylevel 7mm, Unifloor offers years of living enjoyment due to the product's long lifespan, noise reduction and levelling function.



For us at Unifloor, the use of FSC® certified wood is very important. Environmentally and social appropriate use of the forest means that the forest's productivity, biodiversity and ecological processes are maintained while harvesting the wood. By using FSC wood, we are helping to promote responsible forest management. Therefore Unifloor solely uses raw materials from FSC certified sources.

unifloor
UNDERLAY SYSTEMS

PRODUCT SPECIFICATIONS

EASY LEVEL
7 MM BY UNIFLOOR

TECHNICAL DATA

| | |
|------------------------------|-----------------|
| Article number | 190.00 |
| Thickness/tolerance (mm) | 7 / ± 0.2 |
| Size (cm)/tolerance (mm) | 560 x 790 / ± 1 |
| Raw material(s) combinations | MDF/softboard |
| Colour | Natural/brown |

| | |
|---|------|
| Weight per m ² (kg) | 3.4 |
| Weight per package (kg) | 17.9 |
| Density (kg/m ³) | 483 |
| Humidity (%) | 4-10 |
| Swelling after 24 hours in water, max (%) | < 45 |

Fire class

(according to EN13501: 2007)

| | |
|-----------|--------------------|
| Nude test | E _{fl-s1} |
|-----------|--------------------|

| | |
|--|------|
| Thermal resistance R value (m ² .K/W) | 0.12 |
|--|------|

(according to ISO 8302:1991 and EN 12667:2001)

| | |
|--|------|
| Bending strength (kg/cm ²) | > 40 |
|--|------|

(according to EN 310)

Compressive strength (kPa)

(according to EN 826 with 0.5 mm imprint)

352

Impact sound reduction on concrete floor

(according to ISO 10140-3 2010)

| | |
|--|-----------------------|
| in combination with cushion vinyl 3mm | 21 dB ΔL _w |
| in combination with LVT click 4.5 mm | 21 dB ΔL _w |
| in combination with LVT click 5.5 mm (with integrated underlay) | 21 dB ΔL _w |

Impact sound reduction on wooden floor

(according to ISO 10140-3 2010 base from 64 dB)

| | |
|---------------------------------------|-----------------------|
| in combination with cushion vinyl 3mm | 15 dB ΔL _w |
| in combination with LVT click 4.5 mm | 17 dB ΔL _w |

Formaldehyde degree

FSC certified

EPD certified

EPLF standard

E-1

FSC C154437

EPD-Unifloor-257-EN

Complies with minimum standard

MMFA

Complies with minimum standard

APPLICATION

Levelling underlay for LVT click and loose lay, cushion vinyl and carpet tiles for wooden subfloors. 21 db impact sound reducing solution for LVT click and cushion vinyl on fixed concrete floors.

PACK CONTENTS

12 / 12

- 12 base- and 12 topboards
- 560 x 790 mm
- 5.31 m²
- thickness 7 mm

PACKAGING

Installation instructions present

Pallet contents 24 packs / 127.44 m²

Pallet size

(lxwxh) 1200x800x1180 mm

Pallet weight 446 kg



Scan the QR-code
to find out more
about Easylevel®!

Or visit www.unifloor-underlay.com